



Navisafe Curved Disk clean - prepare - peel - stick mounting instruction

as these can contain ingredients that may leave residues on your inflatable fabric that may prevent glues from adhering properly. All applications should be performed between 70°F to 100°F (21°C to 38°C) and in a dry and well ventilated area product. Apply the cleaner/solvent in accordance with the manufacturer's instructions. Avoid general maintanence cleaners Chloride (PVC). It is essential to know the fabric that your inflatable is made of to insure you use the correct cleaning/wiping There are two main types of material used in the manufacture of inflatable boat collar or tubes; Hypalon, and Polyvinyl (3MTM High Performance Acrylic Adhesive 350). Mounting to surfaces at temperatures below 50°F (10°C) is not



- Curved Disk. Determine the location of the provided Navisafe
- Using the Navisafe Curved Disk as a template lightly trace the outline using a pencil.
- area the pad will be mounted. the surrounding fabric area is separate from the Once done mask off the traced outline so that



- Using a light duty sand paper gently abrade the creating an optimul surface for adhesion. masked off area (where mount will be adhered)
- Use a lint free cloth to remove any dust from
- Wipe/Clean the surface of the masked off solvent for your material. mounting area with the appropriate cleaning
- Peel the protective paper from the adhesive on the Navisafe Curved Disk.



- Position the Navisafe Curved Disk to the exact area that you have marked, and have masked off
- Once the Disk is positioned it will be difficult to remove and re-position.



Address: Traneredsvägen 112, 426 53 Västra Frölunda, Sweden Phone: +4631-690380 , post@navisafe.com





Portable navigation lights NAVISAFE



a weight on the mount to insure proper



Navlight models 041 and 341 can be mounted directly to the newly installe Navisafe Curved Disk



Address: Traneredsvägen 112, 426 53 Västra Frölunda, Sweden Phone: +4631-690380 , post@navisafe.com